# Altea 400



## **ALTEA-412-WR**

DAS Audio Group, S.L. - C/ Islas Baleares 24 - 46988 Fuente del Jarro - Valencia - Spain - Tel. +34961340860 Updated (DD/MM/YYYY): 11/10/2024



#### **KEY FEATURES**

- · 2-way, full range system
- ·12" bass loudspeaker
- · 1" compression driver
- · Angled enclosure design for stage monitor use
- · Built-in rigging points
- · Stand mountable

#### **DESCRIPTION**

ALTEA-412 is a passive system designed to deliver exceptional sound quality across a wide variety of applications, from PA systems at medium-sized events to stage monitors and fixed installations. The ALTEA-412 can reproduce frequencies from 68 Hz to 20 kHz and delivers a maximum SPL of 127 dB, making it an exceptionally versatile system.

The system features a powerful 12" transducer with a 2.5" voice coil for reproducing mid and low frequencies. High frequencies are handled by an M-32 compression driver with a 1" voice coil, providing exceptional performance. The diffuser, designed to provide 90° x 60° dispersion, works with the other components to ensure wide and uniform sound dispersion.

ALTEA-412 is constructed from high-quality polypropylene, making it extremely rugged and relatively lightweight, weighing only 14.5 kg (32.0 lbs). Equipped with integrated ergonomic handles and M8 rigging points, this system is easy to transport and install, offering a practical and efficient solution for any sound setup.

The ALTEA-412-WR variant is designed for outdoor use, incorporating improved weather-resistant components. The INOX grille and screws guarantee resistance against rust, and the grille has a triple layer of protection; fabric, foam and water-repellent mesh, which protects against humidity, dust and small water particles, increasing the durability of the components. On the rear side it incorporates a protective cover for the speakON cable that protects the electrical connection from contact with water.

### **ALTEA-412-WR**



### **SPECIFICATIONS**

#### **Performance**

Frequency Range (-10 dB)	68 Hz - 20 kHz
Horizontal Coverage (-6 dB)	90°
Vertical Coverage	60°
Nominal Impedance	8 ohms
RMS Power Handling	300 W
Peak Power Handling	1200 W
On-axis Sensitivity 1W/1 m	96 dB SPL
Maximum Peak SPL at 1 m	127 dB
Recommended Amplifier	PA-900
Connectors	
Audio Input Connector	1 x speakON NL4
Audio Output Connector	1 x speakON NL4
Enclosure	
Enclosure Construction	Polypropylene
Enclosure Geometry	Trapezoidal
Rigging	M8 Rigging Points
Color	Black
Depth	350 mm (13,8 in)

## **ALTEA-412-WR**

DAS Audio Group, S.L. - C/ Islas Baleares 24 - 46988 Fuente del Jarro - Valencia - Spain - Tel. +34961340860 Updated (DD/MM/YYYY): 11/10/2024

Net Weight

Dimensions ( $H \times W \times D$ )



655 x 380 x 350 mm

25,8 x 15,0 x 13,8 in

14,5 kg (32,0 lb)


### Components


LF Driver	12MI
HF Driver	M-32


### **Shipping**


Carton Dimensions ( H x W x D )	750 x 450 x 415 mm 29,5 x 17,7 x 16,3 in
Shipping Weight	17,5 kg ( 38,6 lb )

### **DIMENSIONS**









### ORDERING INFORMATION

Model	Description	P/N
System		
ALTEA-412-WR		10404923
Replacement Parts		

## **ALTEA-412-WR**

DAS Audio Group, S.L. - C/ Islas Baleares 24 - 46988 Fuente del Jarro - Valencia - Spain - Tel. +34961340860 Updated (DD/MM/YYYY): 11/10/2024



12MI	Cone Transducer	10214310
GM-12MI	Recone Kit	20208290
LAMP-F-21	Lamp	30000535
M-32	Compression Driver	20208970
TC-ALT412	Filter	20150070
Accessories		
ANL-1	Rigging Accessories	10101010
ANL-1	Installation & Stacking Acc.	10101010
AX-112-5	Installation & Stacking Acc.	10102390
AXF-X12	Installation & Stacking Acc.	10104831
AXW-ALT-WR	Installation & Stacking Acc.	10102392
FUN-AL712	Transport Accessories	10103780
TRD-6	Installation & Stacking Acc.	10104470
TRD-7	Installation & Stacking Acc.	10104471
TRPD-S2-PAK	Installation & Stacking Acc.	10104011

## **ALTEA-412-WR**

