HQ series







KEY FEATURES

- ·Two-way long-throw system
- · DX finish (Fiberglass) for direct exposure
- · Horn loaded 12" low frequency loudspeaker
- · M-78N neodymium compression driver
- · Selectable passive/biamplified operating modes
- · Wide 90° x 50° coverage angles
- · Rotatable horns
- · Stainless steel rigging kit

DESCRIPTION

HQ-112.95 is a configurable, wide-range passive or bi-amplified two-way system designed for long-throw applications, providing efficient coverage over large distances. It is equipped with a 12" mid-low frequency driver, coupled to a high-Q waveguide to optimize coverage and performance, and an M-78N compression driver with a 1.5" titanium diaphragm. The system is optimized to deliver a clear and precise acoustic response. Additionally, it incorporates two rotatable waveguides, one for mid frequencies and one for high frequencies, facilitating installation in various configurations.

HQ-112.95 covers a frequency range of 80 Hz to 18 kHz, reaching a maximum sound pressure level of 143 dB SPL in passive mode. It has a power handling capacity of 400 W RMS and 1600 W peak in passive mode, with a nominal impedance of 8 ohms. In bi-amplified mode, the system handles up to 400 W RMS for mid frequencies and 150 W RMS for high frequencies.

The system is available in two versions: CX (Covered Exposure), which is protected with an ISO-flex coating both externally and internally, and DX (Direct Exposure), which adds an external fiberglass layer and an internal gel seal for enhanced weather resistance. Both versions comply with the IP54 standard, ensuring durability in demanding environments.

Equipped with M10 rigging points, HQ-112.95 offers controlled coverage of 90° x 50° in large venue, hall, or auditorium configurations and is designed to provide precise horizontal and vertical dispersion.



SPECIFICATIONS

Performance

Frequency Range (-10 dB)	80 Hz – 18 kHz	
Horizontal Coverage (-6 dB)	90°	
Vertical Coverage	50°	
Nominal Impedance	Passive: 8 ohms	
Nominal Impedance MF	8 ohms	
Nominal Impedance HF	8 ohms	
RMS Power Handling	Passive: 400 W	
RMS Power Handling HF	150 W	
RMS Power Handling MF	400 W	
Peak Power Handling	Passive: 1600 W	
Peak Power Handling MF	1600 W	
Peak Power Handling HF	400 W	
On-axis Sensitivity 1W/1 m	Passive: 109 dB SPL	
On-axis Sensitivity 1W/1 m MF	109 dB SPL	
On-axis Sensitivity 1W/1 m HF	109 dB SPL	
Maximum Peak SPL at 1 m	Passive: 141 dB	
Maximum Peak SPL at 1 m MF	141 dB	
Maximum Peak SPL at 1 m HF	137 dB	
	DX-100I-230	
	DX-100I-115	
Recommended Amplifier	DX-80I-230	
	DX-80I-115	




	INTEGRAL-M88 INTEGRAL-MA1604 INTEGRAL-MA1004	
Recommended Processor		
Connectors		
Audio Input Connector	1 x speakON NL4	
Addio Input Connector	Covered Barrier Strip Terminals	
Andia Ontro t Carrierator	1 x speakON NL4	
Audio Output Connector	Covered Barrier Strip Terminals	
Enclosure		
Enclosure Construction	Birch Plywood	
Enclosure Geometry	Trapezoidal	
Rigging	M10 Rigging Points	
Finish	Fiberglass	
Color	Black	
Depth	605 mm (24,0 in)	
Dimensions (H x W x D)	990 x 685 x 605 mm	
	39,0 x 27,0 x 24,0 in	
Net Weight	56,0 kg (123,5 lb)	
Components		
LF Driver	12HQN	
HF Driver	M-78N	
Horn/Waveguide	BCH-9050-7037	
Horry vvaveguide	BCM-7545-7037	



Shipping

Carton Dimensions (H x W x D)	1.070 x 650 x 745 mm 42,1 x 25,6 x 29,3 in	
Shipping Weight	60,5 kg (133,4 lb)	

DIMENSIONS



ORDERING INFORMATION

	2 3 3 3 4 4 3 3 3	.,
System		
HQ-112.95-DX		10432030
Replacement Parts		
12HQN	Cone Transducer	20208890
BCH-9050-7037	Horn	30006308
BCM-7545-7037	Horn	30006311
F-HQ112.64.95	Filter	30009041

Description

HQ-112.95-DX



P/N

Model

GM-12HQ	Recone Kit	20208536
GM-M75N	Diaphragm	20205080
M-78N	Compression Driver	20208860
Accessories		
ANL-2	Rigging Accessories	10101020
AX-HQ-X12	Rigging Accessories	10107001
JP-HQ-112	Rigging Accessories	10107003
UFB	Rigging Accessories	10105040

